

Sanitarios y Suites de Baño

Serie Relax



La alta velocidad de rotación de la bomba de vórtice y el diseño geométrico de la tubería de todos los equipos Planus permiten crear un gran vacío capaz de eliminar el agua y los residuos orgánicos de la taza. El alto nivel de rendimiento garantizan la máxima flexibilidad en la planificación de la ruta de las mangueras de descarga, que le permite alcanzar distancias y alturas importantes.

| Serie Relax | |
|--------------|---|
| Referencia | Descripción |
| PLRELAX-12V | WC RELAX 12V (SEDILE MULTIFUNZIONE GEBERIT TUMA INCLUSO) |
| PLRELAX-24V | WC RELAX 24V (SEDILE MULTIFUNZIONE GEBERIT TUMA INCLUSO) |
| PLRELAX-230V | WC RELAX 230V (SEDILE MULTIFUNZIONE GEBERIT TUMA INCLUSO) |

TECHNICAL SPECIFICATION OF THE MAIN COMPONENTS

Vortex Discharge Pump

Hydraulic performances: up to 9 m vertically, up to 80 m horizontally

| | | | |
|------------|--------|--------|---------|
| Voltage | 12 Vdc | 24 Vdc | 230 Vac |
| Absorption | 35 A | 25 A | 3 A |

Inlet Electrovalve

DIRECT ACTING Version (for both fresh water and sea water inlet systems)

| | | | |
|------------|--------|--------|---------|
| Voltage | 12 Vdc | 24 Vdc | 230 Vac |
| Absorption | 80 W | 80 W | 80 W |

SERVO PILOTED Version (for fresh water inlet only)

| | | | |
|------------|--------|--------|---------|
| Voltage | 12 Vdc | 24 Vdc | 230 Vac |
| Absorption | 15 W | 15 W | 15 W |

Independent Inlet Pump

| | | | |
|------------|--------|--------|---------|
| Voltage | 12 Vdc | 24 Vdc | 230 Vac |
| Absorption | 3.6 A | 1.8 A | |

Centralized Inlet Pump (not supplied)

Recommended specifications Working Pressure Min 1 bar—Max 3 bar



Discharge pressure 0.9 bar (9m)



Up to 80 m



CONNECTIONS

Hydraulic Connections

| | |
|--------|------------------------------|
| Inlet | Hose with ID of 20 mm (3/4") |
| Outlet | Hose with ID of 40 mm (1/2") |

Electrical Connections

| | | | |
|------------------------------|-------------------------------|-------------------------------|----------------------------------|
| Voltage | 12 Vdc | 24 Vdc | 230 Vac |
| Minimal wire gauge up to 5 m | 6 mm ² (9 AWG) | 4 mm ² (11 AWG) | 0.75 mm ² (18 AWG) |
| Minimal wire gauge over 5 m | 10 mm ² (7 AWG) | 6 mm ² (9 AWG) | 1 mm ² (17 AWG) |

INFO

| | |
|-----------------------------------|--|
| Weight: | 26kg (High Version) - 23.5 kg (Short Version) |
| Average Water Consumption: | 1.5 l |
| Color: | White (black or bone optional) |
| Seat: | Wood covered with casting resin |
| Hinges: | Stainless steel (soft closing system optional) |
| Integrated bidet: | Optional |