

SKYVENETIAN 16 mm & 25 mm Aluminium slat

Order Form and Product Guide

Customer _____
 Address _____

Tel _____
 Mobile _____
 Email _____

Order _____
 Quote _____
 Date _____
 Project Name _____
 Project Location _____

Are any of the blinds on this order to be installed where children under 42 months old are likely to be allowed? ² **Yes** **No**

Window ID	Dimension Info	Slat Options	Restraint Options
	Type Recess ¹ Blind	Size (mm) 16 25	Guide wire Free hanging Chrome dome Nickel dome Chrome flush Black flush Nickel flush
Location	Width	Colour	
	Drop		
	Installation ² Height		

Manual Control Options <i>Please choose one only</i>			
Option 1 continuous cord ³		Option 2 Lift & Tilt	
Position	Left Right	Lift cord options	Tilt Wand options
		Position	Position
		Left Right	Left Right
Length (mm) ⁴	400 500 700 1000	Metal Cleat <i>(With black or white rubber insert)</i> Chrome - Black White Nickel - Black White	Length (mm) 150 300 1000 Custom Length
Cord Colour	Black Grey Fawn White		
Cord Tidy <i>(With black or white rubber insert)</i>	Chrome - Black White Nickel - Black White		

Powered Control Options	Qty
Motor Code _____	
Wire exit point: Left Right	
Switches Transformers or Controls Required: Yes ⁵ No	

Notes:

- If recess size is specified the blind will be made X minus 10 mm[3/8"] and Y minus 5 mm[1/4"].
- Installation height required for cord operated blinds. EN13120 Standards demand the distance from the floor to the bottom of the pull cord(s) shall be at least 1500 mm [59 1/16"] and a cord collection device (cleat or cord tidy) is fitted at or above this height. We can only supply blinds meeting these conditions unless the above question has been answered No.
- Continuous cords are supplied with cord tidy child safety device as standard, please select colour.
- Installation height less cord length must be greater than 1500 mm [59 1/16"].
- Please fill in the Powered Accessories Order Form.

A selection of simple shapes are available, please contact Dometic for more details.

Motor codes & specifications (Other motors available please contact manufacturer for details)

Voltage	Motor Code	Description	Switched (SW) or remote (R)	Torque Nm	RPM	Min X (mm)	Max drop (mm)	Slat Size		Head rail size	
								16mm	25mm	25mm	50mm
12v DC	25SD1	Atlantic 12S - 12v Double End	SW	1.2	32	650 mm [25 9/16"]	3250 mm [127 15/16"]	✓	✓	✓	N/A
24v DC	25SD2	Atlantic 24S - 24v Double End	SW	1.2	32	650 mm [25 9/16"]	3250 mm [127 15/16"]	✓	✓	✓	N/A
24v DC	24	Somfy Lw25-B83	SW	0.8	30	662 mm [26 1/16"]	3250 mm [127 15/16"]	✓	✓	✓	N/A
24v DC	S30D/S30R	Somfy Sonesse 30 DCT / RTS	SW / R	2	28	616 mm [24 1/4"]	TBC	N/A	✓	N/A	✓
110V AC	S40W1/S40R1	Somfy Sonesse 40 WT / RTS	SW / R	9	14	616 mm [24 1/4"]	TBC	N/A	✓	N/A	✓
240v AC	S40W/S40R	Somfy Sonesse 40 WT / RTS	SW / R	9	12	616 mm [24 1/4"]	TBC	N/A	✓	N/A	✓
230v AC	40W4	Pacific 230R WT 230v AC	SW	10	16	616 mm [24 1/4"]	3250 mm [127 15/16"]	N/A	✓	N/A	✓

Internal use only Customised



SKYVENETIAN 16 mm & 25 mm Aluminium slat

Order Form and Product Guide

Cleats

Mandatory child safety device

Fix to an adjacent wall. Secure cord after every operation of blind.

Available in Chrome or Brushed Nickel with either a White or Black rubber insert.



Cord Tidy

Mandatory child safety device

Fix to an adjacent wall, ensures taut chain or continuous cord.

Available in Chrome or Brushed Nickel with either a White or Black rubber insert.



Cord connector

Mandatory child safety device for Manual blinds

Best matched to slat colour

Black Brown Dark Grey
Light Grey Beige White

Breaks under horizontal force, releasing cords.



Tilt wand

Used to tilt the blind slats

Colours:

Black Blue Grey
Beige White



Acorn

A synthetic rubber handle, also used as an handle for the lift cord.

Colours:

Black Blue Grey
Beige White

Where used, the rubber handle is colour matched to slat as close as possible.



Head rail

A 25mm steel headrail is used as standard and is available in the following standard colours.

White Black Brown
Vanilla Silver

An aluminium headrail and custom painting service are both available upon request, please contact Dometic direct for more details.

Guide wire hold down options

Dome: Chrome or Brushed Nickel

Flush Mounted: Chrome, Brushed Nickel or Black

