# **SKYVENETIAN** 50mm Wood slat

## **Order Form and Product Guide**

Customer		Tel		Order	Quote	Date
Address		Mobile		Project Name		
		Email		Project Location		
Are any of th	ne blinds on this order to be installed where children under 42	months ol	d are likely to be allowed? <sup>2</sup> Yes No			

re any of the blinds on this order to be installed where children under 42 i							
Window ID	Dimension Info	Slat	Head rail Options	Restraint Options			
	Туре	Colour	Туре	Free hanging			
	Recess 1		50 mm	Guide wire			
	Blind		_	Chrome dome			
Location	M. 44 (M)		Powered Only	Nickel dome			
200411011	Width (X)	Ladder	LTWN	Chrome flush			
		String	Fixing	Black flush			
	Drop (Y)	Tape:	Тор	Nickel flush			
		24 mm	Face	0:			
		- 38 mm		Sidetrack			
	Installation		Colour	Sidetrack colour			

Sidetrack colour

White Black

RAL Ref

Custom

		Ma	anual Contro	l Options	Please choose	one only				
Option 1 Option 2 Lift & Tilt						Powered	Qty			
Cord Loop <sup>3</sup>			Lift option		Tilt Options		Control Options	Qiy		
Position:	Left	Right	Position	Left	Right	Tilt Cord	l site end to	lift cord)	Motor Code	
Length (m		500	Acorn Type		(default)	Tilt wan	d		Wire exit point:	
	400 700	500 1000		Square	Round		Left	Right		h+
Cord Colo	ur					Туре			Left Rig	nt
Black Fawn	Gre Whit	,				Length r	Rubber nm 300	Wood 1000	Switches Transformers or	
Metal Cord Tidy (With black or white rubber insert) Chrome - Black White Nickel - Black White				-	Custom Length		Controls Required  Yes 5	No		

#### Notes

height<sup>2</sup>

- 1. If recess size is specified the blind will be made X minus 10 mm[3/8"] and Y minus 5mm[1/4"].
- 2. Installation height required for cord operated blinds. EN13120 Standards demand the distance from the floor to the bottom of the pull cord(s) shall be at least 1500 mm [59 1/16"].and a cord collection device (cleat) is fitted at or above this height. We can only supply blinds meeting these conditions unless the above question has been answered No.
- 3. Cord Loop is supplied with a cord tidy child safety device as standard, please select colour.
- 4. Installation height less cord length must be greater than 1500 mm [59 <sup>1/16</sup>"].
- 5. Please fill in a Powered Accessories Order Form, download from <a href="here">here</a>.
- 6. Specialist motor please contact manufacturer before ordering.
- A selection of simple shapes are available, please contact manufacturer for more details.
- Wood Venetian blinds are not suitable in areas of high humidity, toilets, bathrooms or wet rooms. Please consult manufacturer regarding alternative solutions for these areas.

Motor codes & specifications (Other motors available please contact manufacturer for details)

Valtage Mater Code		December 2	Switched (SW) or	Torque	DD14	Min width	Max drop	Head rail size	
Voltage	Motor Code	Description	remote controlled (R) Nm RPM X (mm)		X (mm)	Y(mm)	50mm	TWIN	
12v DC	25SD1	Atlantic 12S - 12v Double End	SW	1.2	32	650 mm [25 9/16"]	3250 mm [127 15/16"]	<b>✓</b>	N/A
24v DC	25SD2	Atlantic 24S - 24v Double End	SW	1.2	32	650 mm [25 9/16"]	3250 mm [127 15/16"]	<b>✓</b>	N/A
24v DC	24	Somfy Lw25-B83	SW	1	30	662 mm [26 <sup>1/16</sup> "]	3250 mm [127 <sup>15/16</sup> "]	✓	N/A
24v DC	LTWN	Lutron Twin	See note 6	See note 6	See note 6	624 mm [24 9/16"]	3250 mm [127 15/16"]	N/A	✓
24v DC	S30D / S30R	Somfy Sonesse 30 DCT / RTS	SW/R	2	28	616 mm [24 <sup>1/4</sup> "]	TBC	✓	N/A
230v AC	S40W/ S40R	Somfy Sonesse 40 WT / RTS	SW / R	9	12	616 mm [24 <sup>1/4</sup> "]	TBC	<b>✓</b>	N/A
230v AC	40W4	Pacific 230R WT 230v AC	SW	10	16	616 mm [24 <sup>1/4</sup> "]	3250 mm [127 <sup>15/16</sup> "]	✓	N/A

Customised Internal use only

DOMETIC

**♦** DOMETIC CHILD

SAFE Y

# **SKYVENETIAN** 50mm Wood slat

## Cleats CHLD

### Mandatory child safety device

Fix to an adjacent wall. Secure cord after every operation of blind.

Available in Chrome or Brushed Nickel with either a White or Black rubber insert.



## Cord Tidy

#### Mandatory child safety device

Fix to an adjacent wall, ensures taut chain or continuous cord.

Available in Chrome or Brushed Nickel with either a White or Black rubber insert.



## Cord connector Sure V

#### Mandatory child safety device for manual blinds

Best matched to slat colour

Black

White

Breaks under horizontal force, releasing cords.



#### **Tilt Wand**

Used to tilt the blind slats

Colours:

Black Blue Grey

Beige White



#### **Wood Tilt Wand**

Colours:

Black Golden Oak Red Mahogany

Cherry Honey Oak Teak
Dark Mahogany Maple White
Ebony Natural USA Walnut

European Walnut Off White



## **Order Form and Product Guide**

## Acorns

#### **Wooden Square or Round**

Standards Colours:

Black Red Mahogany Maple
Ebony American Walnut Natural
European Walnut Cherry Off White
Dark Mahogany Honey Oak White



## **Guide wire Hold down options**

**Dome:** Chrome or Brushed Nickel

Flush Mounted: Chrome, Brushed Nickel or Black



## **Head rail Colour Options**

		VB50	TWIN
	White	✓	<b>✓</b>
Standard	China White	✓	
Colour	Black	✓	
	Brown	✓	
	Beige	✓	

Custom colours are available, contact manufacuter for more details

