



BLINDS WITHOUT CORD HOLES



Dometic Oceanair Skysol Honeycomb offers superior light control. With no visible cording holes to the face of the fabric, you can achieve a thorough blackout coverage for a great night's sleep and complete privacy. On top of that, the Skysol Honeycomb has a range of fabric and colours to choose from. Its slim profile makes it ideal for slim recesses. Powered operation is available with 12 V DC, 24 V DC or mains motors, operated by hand held remote, or integration into the control system.

BENEFITS WITH SKYSOL HONEYCOMB

- Suitable for slim recesses
- Choice of fabric types and colours
- Powered operation available with 12 V DC, 24 V DC or mains motors
- Hand held remote, wall switch or integration into the control system
- Available with white, beige or grey hardware
- Suitable for inclines
- No visible cording holes

SPECIFICATIONS

POWERED CONTROLS	Custom Powered & Headrail Options Available					
MANUAL CONTROLS	Pull Cord					
	Fixed Handle					
FABRIC	Honeycon	nb (Simple Shapes)	Priva	су		
	Collection	Specified	Black	cout		
HARDWARE	Beige					
	White					
	Graphite					
FIXINGS	Face Fix					
	Top Fix					
RESTRAINTS	Free Hang	lling				
	Guide Wir	es				
HOLD DOWNS	Chrome D	ome				
	Footplates	5				
SHAPING OPTIONS	Rectangle					
	Rectangle W/ Corner Cut					
	Acute Edge					
	Low Acute					
	Inverted Tr					
	Scalene Triangle					
	Right-Ang					
	Rectangle					
	Rectangle W/ Sloped Bottom					
			DB			
ANGLE SUITABILITY		(0°)		(30° - 60°)		
	AO-DB		PB	(30° - 60°)		
	AO-DBE			(60° - 90°)		
	AB	(0° - 30°)				



BLINDS WITHOUT CORD HOLES



SKYSOL HONEYCOMB PLEASE USE AS GENERAL GUIDE FOR SHAPED O TECHNICAL DATA	OPTIONS				
PRODUCT CODE: PB2H	MANUAL		POWERED		
Min Width (X)	106mm (4 ^{3/4} ")	106mm (4 ^{3/4} ") 306m			
Min Width (X) Type AO Blinds	N/A	N/A 506mm (19 ^{15/16°})			
Min Drop (Y)	100mm (3 ^{15/16} ")				
Max Area (Sq.M.)	4		N/A		
Max Width (X)	4400mm (173 ^{1/4} °)				
	If Width (X) ← 1000mm	If Width (X) 100	lmm → 2700mm	If Width (X) 2701mm → 4400mr	
Max Drop (Y)	5200mm (204 ^{3/4} ")	3500mm (137 ^{13/16} ")		2200mm (86 ^{5/8} ")	
	Headrail Fitting Allowance Depth				
Top Fix	50mm (2")			70mm (2 ^{3/4"})	
Face Fix	26mm (1")	33mm (1 ^{5/16} ")			

